

HWKSF-10



17.3" LCD Console Drawer

Specifications

Specifications	HWKSF-10
Panel	17.3" TFT-LCD with LED Backlight
Active Display Area (mm)	381.888 X 214.812 (mm)
Pixel Pitch (mm)	0.1989 (H) x 0.1989 (V)
Resolution	1920 x 1080
Display Color	262K (RGB 6-bit)
Color Pixel Arrangement	RGB Vertical Strip
Display Mode	Normally White
Brightness (cd/m²)	300
Contrast Ratio	500:1
Hot Key Control	OSD Hot Key
User Control	OSD Control (Auto Saving)
Input Signal	RGB Analog, H/V Separate
Plug-n-Play VESA	VESA DDC 2B
Power Consumption	13.2W
Viewing Angle(Typical)	- 70∼ 70(H)
	- 60~ 60(V)
Power	Full range, 100V AC to 240V AC
Approval	CE, FCC for the Product. UL, TUV, CE for Power Supply

▶ Features

- Modularized KVM switch design.
- Flip-open LCD panel supports resolution of Full HD 1920x1080 .
- For managing computers with PS/2, USB, Mac or Sun interface.
- For rack cabinet with depth from 20" (50cm) and up (with appropriate Rear bracket & extension kit).
- Standard 19" 1U rack drawer.
- Locking mechanism locks the drawer when pulled out, pushed in, or folded down.
- Full 105 key, low-profile, sturdy keyboard included.
- A universal C-36 connector for connection between console drawer and Integra KVM switch module.
- User-replaceable keyboard with various languages support
- User-replaceable touch pad for easy replacement
- Touch pad with simulated wheel control
- Supports Sun keyboard mapping and Mac keyboard mapping.
- Ultra sturdy, tilt-free, two-piece Rear Bracket and Extension design.



	HWKSF-10 (17.3")
Keyboard Replaceable	Yes
Touch Pad Replaceable	Yes
Module Selection	Yes
H x W x D (mm)	44 x 440 x 565

